

TECHNICAL FEATURES


- Type of sensor: rotary potentiometer;
- Accuracy: +/- 0.1% F.S.;
- Linearity: +/- 0.5 % F.S.;
- Resolution: virtually infinite;
- Output signal: 4-20 mA;
- Measuring range: 1800, 2300, 3300, 4300, 4800, 5300, 6300, 7300, 8000, 8300;
- Power supply: +10...30 VDC;
- Protection level: IP 67;
- Operating temperature:-40°/+85°C;
- Wire: AISI 316 stainless steel nylon coated;
- Case material: PBT;
- Wire tension: 6.4 N (+/- 30%);
- Shock: 50 G, 11 m/s.




longitudinal section



top view



Cross section





The wire crack meter consists of a sturdy case in polymer designed to withstand harsh environments conditions. Each sensor is provided with a mounting bracket to fit all types of installations (see the figure).

Measuring length available from 1800 mm to 8300 mm. Ideal for monitoring unstable slopes and rocks, brickwork.

Technically, any movement of the steel

wire anchoring point, which is tensioned through a device applying about 6.4 N force, causes a variation in the electrical signal proportional to the displacement of the wire itself.

	DIMENSIONS
case dimensions	142 x 80.5 x 100 mm
wire dimension	0.85 mm

